

Double End Nutrunners

Clecomatic Clutch & Stall

Cleco®

34 Series

Torque Range

5 - 103 Nm 4 - 76 Ft. Lbs.

Bolt Size

M5 - M36 #10 - 1 1/2"

External torque adjustment (Clecomatic models)

Indexable anglehead

One torque spring to meet specified range

Oilless blades 

Reversible



34RAA33D24

Model Number	Square Drive	Free Speed RPM	Torque		Length		Weight		Anglehead				
			ft.-lbs.	Nm	in.	mm	lbs.	kg	Height		Side to Center		
										in.	mm	in.	mm
Clecomatic - Lever Start - Reversible													
34RAA09D24	1/2"	1825	4-7	5-9	17.8	452	4.5	2.0	1.69	43	0.67	17	
34RAA16D24	1/2"	1055	7-12	9-16	17.8	452	4.5	2.0	1.69	43	0.67	17	
34RAA28D24	1/2"	645	10-20	14-28	18.8	478	4.7	2.1	1.69	43	0.67	17	
34RAA33D24	1/2"	540	12-24	17-33	18.8	478	4.7	2.1	1.69	43	0.67	17	
34RAA47D24	1/2"	380	17-35	24-47	19.0	483	5.1	2.3	1.69	43	0.67	17	
34RAA53D24	1/2"	265	17-39	24-53	19.0	483	5.1	2.3	1.69	43	0.67	17	
34RAA67D34	1/2"	265	24-49	33-67	20.5	521	5.8	2.6	2.32	59	0.87	22	
34RAA94D34	1/2"	185	35-69	47-94	20.5	521	5.8	2.6	2.32	59	0.87	22	
Stall - Lever Start - Reversible													
34RAS10D24	1/2"	1825	7	10	17.8	452	4.2	1.9	1.69	43	0.67	17	
34RAS18D24	1/2"	1055	13	18	17.8	452	4.2	1.9	1.69	43	0.67	17	
34RAS30D24	1/2"	645	22	30	18.8	478	4.4	2.0	1.69	43	0.67	17	
34RAS40D24	1/2"	480	29	40	19.0	483	4.4	2.0	1.69	43	0.67	17	
34RAS52D24	1/2"	380	38	52	19.0	483	4.4	2.0	1.69	43	0.67	17	
34RAS58D34	1/2"	335	43	58	20.5	521	5.5	2.5	2.32	59	0.87	22	
34RAS73D34	1/2"	265	54	73	20.5	521	5.5	2.5	2.32	59	0.87	22	
34RAS103D34	1/2"	185	76	103	20.5	521	5.5	2.5	2.32	59	0.87	22	

GENERAL:

Air Inlet: 3/8" NPT
 Minimum Hose Size: 5/16"
 Tool performance rated at 90 psi (620kPa) air pressure.

STANDARD EQUIPMENT:

Operating instructions & service manual
 Suspension bail
 Exhaust Overhose
 Clutch adjustment tool (Clecomatic tools)

OPTIONAL EQUIPMENT:

Assembly wrench: 201898
 Torque signal kit: 201900
 Non-reversible kit: 204999
 Mounting plates: D2 tools 43287131
 D3 tools 49098103

Additional accessories: Page 57