

Impact Wrenches

Inline & Pistol Grip

Cleco®

Torque Range:
20 – 2450 Nm
15 – 1800 Ft. Lbs.

Bolt Size:
M10 – M30
7/16 – 1 1/2"

- Lever and trigger start
- Reverse or forward bias
- 6" extended and spline drives available



Model Number	Bolt Size		Square Drive	Recommended Torque Range		Impacts Per Minute	Free Speed RPM	Length		Weight		Side to Center	
	GR. 5 in	GR. 9.8 mm		ft.-lbs.	Nm			in.	mm	lbs.	kg	in.	mm

Inline – Lever Start

WL-200-BQ	7/16	M10	7/16*	15-50	20-68	3,200	3,000	8.5	216	3.1	1.4	1	25
WL-200-3	7/16	M10	3/8	15-50	20-68	3,200	3,000	8.5	216	3.1	1.4	1	25
WL-200-4	1/2	M10	1/2	15-60	20-81	3,200	3,000	8.5	216	3.4	1.5	1	25

Pistol Grip – Trigger Start

WP-200-BQ	7/16	M10	7/16*	15-50	20-68	3,200	3,000	6.5	165	3.4	1.6	1	25
WP-200-3	7/16	M10	3/8	15-50	68-20	3,200	3,000	6.5	165	3.4	1.5	1	25
WP-200-4	1/2	M10	1/2	15-60	20-81	3,200	3,000	6.5	165	3.4	1.5	1	25
WP-455-4R	1/2	M20	1/2	37-370	50-502	1,400	6,500	7	176	5.3	2.4	–	–
WP-455-4P***	1/2	M20	1/2	37-370	50-502	1,400	6,500	7	176	5.3	2.4	–	–
WP-2050-6	7/8	M20	3/4	125-600	170-800	1,000	6,000	6.4	162	7.8	3.5	1.6	42
WP-2060B-6	1 1/8	M24	3/4	250-700	350-950	1,000	4,000	7.8	197	12	5.4	1.8	46
WP-2060B-8	1 1/8	M24	1	250-900	350-1200	1,000	4,000	7.8	197	12.1	5.5	1.8	46
WP-2110B-8	1 3/8	M30	1	750-1650	1000-2250	880	4,600	9.5	241	20.8	9.4	2.2	56

Pistol Grip – Trigger Start – Biased Reverse Power****

WP-2049-6	7/8	M20	3/4	125-550	170-750	1,000	6,200	6.4	162	7.8	3.5	1.6	42
WP-2059-6	1 1/8	M24	3/4	250-700	350-950	1,000	4,000	7.8	197	12	5.4	1.8	46
WP-2059-8	1 1/8	M24	1	250-800	350-1100	1,000	4,000	7.8	197	12.1	5.5	1.8	46
WP-2059-8-6E**	1 1/8	M24	1	250-750	350-1000	1,000	4,000	13.8	350	14.3	6.5	1.8	46
WP-2109B-8	1 3/8	M30	1	750-1650	1000-2250	880	4,300	9.5	241	20.8	9.4	2.2	56
WPS-2109B	1 3/8	M30	#5 SPLINE	750-1800	1100-2450	880	4,300	9.8	248	21.3	9.6	2.2	56

* Quick change chuck
** 6" Extended spindle
*** Pin retainer
****Breakaway torque capacity in reverse:
2049 Series: 750 ft.-lbs. (1000 Nm)
2059 Series: 1200 ft.-lbs. (1600 Nm)
2109 Series: 2500 ft.-lbs. (3400 Nm)

GENERAL:
Air Inlet: 1/4" NPT (WL-200, WP-200, WP-455 series) 3/8" NPT (WP-2049, WP-2050, WP-2059, WP-2060 series) 1/2" NPT (WP-2109, WP-2110 series)
Min. Hose Size: 1/4" (WL-200, WP-200, WP-455 series) 3/8" (WP-2049, WP-2050, WP-2059, WP-2060 series)
Tool performance rated at 90 psi (620kPa) air pressure.

STANDARD EQUIPMENT:
Operating instructions & service manual

OPTIONAL EQUIPMENT:
Additional accessories: Page 72

Cleco®

Torque Range:
1000 – 4000 Nm.
750 – 3000 Ft. Lbs.

Bolt Size:
M30 – M36
1 3/8 – 1 1/2"

- Inside or outside lever
- Positive lock socket retainer (spline drive)
- Multiposition dead handle
- Oil foam bath
- Reverse or forward bias



Model Number		Suitable for Bolt Size		Square Drive	Recommended Torque Range		Impacts Per Minute	Free Speed RPM	Length		Weight		Side to Center		
Inside Trigger	Outside Trigger	in.	mm	in	ft.-lbs.	Nm			in.	mm	lbs.	kg	in.	mm	
Trigger Start - Spade handle															
WT-2110-8		1 1/2	M30	1	750-1650	1000-2250	880	4,600	12.9	327	21	9.5	2.2	56	
WTS-2120		1 1/2	M36	#5 Spline	1200-2800	1600-3800	850	3,300	14.3	362	27.6	12.5	2.3	59	
WT-2120-12	W-2120-12	1 1/2	M36	1 1/2	1200-3000	1600-4000	850	3,300	14.3	362	27.6	12.5	2.3	59	
Trigger Start - Spade Handle - Biased Reverse Power**															
WT-2109-8-6E*		1 3/8	M30	1	750-1550	1000-2100	880	4,300	18.9	479	24.6	11.2	2.2	56	
WT-2109-8	W-2109-8	1 3/8	M30	1	750-1650	1000-2250	880	4,300	12.9	327	21	9.5	2.2	56	
WTS-2109		1 3/8	M30	#5 Spline	800-1800	1100-2450	880	4,300	13.1	333	21.5	9.8	2.2	56	
WT-2119-12		1 1/2	M36	1 1/2	1200-2600	1600-3500	820	3,300	14.3	362	29	13.1	2.3	59	
WTS-2119	WS-2119	1 1/2	M36	#5 Spline	1200-2500	1600-3400	820	3,300	14.25	362	29	13.1	2.3	59	

*6" Extended spindle

**Breakaway torque capacity in reverse:
2109 Series: 2500 ft.-lbs. (3400 Nm)
2119 Series: 3500 ft.-lbs. (4700 Nm)

GENERAL:

Air Inlet: 1/2" NPT
Min. Hose Size: 1/2" (WP-2109, WP-2110 series) 1/2" NPT (WP-2109, WP-2110 series) 5/8" (WP-2119, WP-2120 series) Tool performance rated at 90 psi (620kPa) air pressure.

STANDARD EQUIPMENT:

Operating instructions & service manual
Dead handle bracket
Dead Handle

OPTIONAL EQUIPMENT:

Additional accessories: Page 72