

Inline Grinders

For Cone or Plug Wheels

Cleco®

9,000 – 24,000 RPM

0.8 – 2.1 hp (0.6 – 1.6 kW)

- Governed and non-governed models
- Side exhaust
- Extended Series
- Rugged steel housings



Model Number		Free Speed rpm	Abrasives Capacity	Type Housing	Weight		Length		Spindle Size	Air Inlet Size
Rear Exhaust	Rotatable Side Exhaust				lbs.	kgs	in.	mm		
136 Series Extended – 0.8 hp (0.6 kW) – Non-Governed – Side Exhaust										
136GEL-240-P3T		24,000	1 1/4" Cone or Plug Wheel	S	3.5	1.6	12.3	312	3/8"-24	1/4"
15 Extended Series – 1.2 hp (0.9 kW) – Governed – Rotatable Exhaust Deflector										
15GELC-180-P3T		18,000*	2" Cone or Plug Wheel	S	4.3	2.0	14.5	368	3/8"-24	1/4"
15GELC-180-P5T		18,000*	2" Cone or Plug Wheel	S	4.5	2.0	14.9	378	5/8"-11	1/4"
15GELC-140-P3T		14,000*	2" Cone or Plug Wheel	S	4.3	2.0	14.5	368	3/8"-24	1/4"
500B Horizontal Series – 2.1 hp (1.6 kW) – Governed – Rotatable Exhaust Deflector										
590BHL-P		9,000*	3" Cone or Plug Wheel	S	7.6	3.4	17.9	455	5/8"-11	1/4"
5120BHL-P		12,000*	3" Cone or Plug Wheel	S	7.6	3.4	17.9	455	5/8"-11	1/4"

Housing Guide: A=Aluminum, C=Composite, S=Steel
*Governor controlled speeds

GENERAL:

All tools performance rated @ 90psi (620 kPa) air pressure.
Minimum Hose I.D.- 136, 15, 500B Series: 5/16" (7.9mm)

STANDARD EQUIPMENT:

Applicable wrenches, operating instructions & service manual

EXTRA EQUIPMENT:

See pages 28–31
Overhose (rear exhaust): See page 63

Refer to Page 7 for description of Rapid Select.