

# Inline Grinders

For Type 1 Wheels

## Cleco®

6,000 – 18,000 RPM

0.5 – 4.1 hp (0.4 – 3.1 kW)

- Short & extended
- Side & rear exhaust
- Safety lever or spade handle



Model Number		Free Speed rpm	Type 1 Capacity	Type Housing	Weight		Length		Arbor/ Spindle Size	Air Inlet Size
Rear Exhaust	Rotatable Side Exhaust				lbs.	kgs	in.	mm		
<b>136 Series – 0.5 hp (0.4 kW) – Rear Exhaust</b>										
136GLR-180-W3T4		18,000	3" x 1/2" (4" wheel guard)	S	2.4	1.1	7.3	185	3/8"-24	1/4"
136GLR-150-W3T4		15,000	3" x 1/2" (4" wheel guard)	S	2.4	1.1	7.3	185	3/8"-24	1/4"
<b>500B Series – 1.9 hp (1.4kW) – Rotatable Exhaust</b>										
560BHL-16		6,000	6" x 1" (6" wheel guard)	S	10.8	4.9	18.4	467	5/8"	1/2"
<b>500B Series – 1.9 hp (1.4kW) – Rotatable Exhaust – Spade Handle</b>										
560BHX-16		6,000	6" x 1" (6" wheel guard)	S	11.6	5.3	18.8	478	5/8"	1/2"
<b>1700 Series – 3.1 hp (2.3kW) – Lock-off Lever Throttle</b>										
1760HL-16		6,000*	6" x 1" (6" wheel guard)	S	14.5	6.6	19.6	498	5/8"	1/2"
<b>1900 Series – 4.1 hp (3.1 kW) – Spade Handle</b>										
1960HG-16		6,000*	6" x 1" (6" wheel guard)	S	6.8	7.6	21.4	544	5/8"	1/2"

Housing Guide: A=Aluminum, C=Composite, S=Steel

\* Governor controlled speeds

### GENERAL:

All tools performance rated @ 90psi (620 kPa) air pressure.  
Minimum Hose I.D.– 560, 1700, 1900 Series: 1/2" (12.7mm)

### STANDARD EQUIPMENT:

136, 500B, 1700 & 1900 series: Wheel guard and flange wrench

### EXTRA EQUIPMENT:

See pages 24–27

Wheel Guards: See page 27

Overhose (rear exhaust): See page 63

Refer to Page 7 for description of Rapid Select.