

# Inline & Right Angle Drills

## DOTCO®

500 – 28,500 RPM

0.3 – 0.4 hp (0.22 – 0.30 kW)

- Wide selection of tools to match your application
- Rear exhaust
- Select geared models available



### New! Ergonomic Safety Lever

Beginning July 2004, all Dotco "S" tools will be shipped with our new comfort grip safety lever.



Model Number	Free Speed rpm	Drill Diameter Capacity	Type Housing	Weight		Length		Head Ht.		Chuck Size	Air Inlet Size
				lbs.	kgs	in.	mm	in.	mm		
<b>Inline 15LF Series – 0.4 hp (0.30 kW)</b>											
15LF081-38+	5,300	1/4"	C	1.4	0.6	8.0	203	-	-	1/4"	1/4"
15LF082-38+	4,000	1/4"	C	1.4	0.6	8.0	203	-	-	1/4"	1/4"
15LF083-38+	3,300	1/4"	C	1.4	0.6	8.0	203	-	-	1/4"	1/4"
15LF087-38+	600	1/4"	C	2.0	0.9	9.3	236	-	-	1/4"	1/4"
<b>Right Angle 15-14 Series – 0.3 hp (0.22 kW)</b>											
15L1489-38	3,600*	1/4"	C	1.5	0.7	8.0	203	3.0	76	1/4"	1/4"
15L1488-38	2,400*	1/4"	C	1.5	0.7	8.0	203	3.0	76	1/4"	1/4"

Housing Guide: A=Aluminum, C=Composite, S=Steel

\* Planetary geared

+ Model available without chuck. Replace -38 with -40.

#### GENERAL:

All Tools performance rated @ 90psi (620 kPa) air pressure.

Minimum Hose I.D.– 15LF, 15-14 Series: 1/4" (6.4mm)

15-29 Series: 5/16" (7.9mm)

#### STANDARD EQUIPMENT:

Jacobs geared chuck, chuck key, dead handle (all inline models with chuck size greater than 1/4").

#### EXTRA EQUIPMENT:

For lock-off safety lever, substitute "S" for "L" in model number.

Overhose (rear exhaust): See page 63

Dead Handle: 539602

Refer to Page 7 for description of Rapid Select.