

Random Orbital Sander

- 10,000 RPM
- Precise feathering throttle produces a better finish
- Built in air regulator for maximum operator control
- Easy replacement of eccentric bearing and spindle assembly



Heavy Duty High Speed Disc Sander

- Ideal for feather edging, light sanding and rust removal
- Designed to sand contours and hard to reach areas
- Variable speed regulator for on-the-job adjustment
- Ergonomic grip for operator comfort
- Lower dBA and lighter than competitive models



| Model Number | Free Speed | Disc Capacity | Spindle Size | Length | | Weight | | Hose Size | | Air Consumption (CFM) | Air Inlet (NPT) |
|-------------------------------|------------|---------------|--------------|--------|-----|--------|-----|-----------|-----|-----------------------|-----------------|
| | | | | in. | mm | lbs. | kg | in. | mm | | |
| Orbital/Random Orbital | | | | | | | | | | | |
| MP4415 | 10,000 | 5" | - | - | - | 3.2 | 1.5 | 1/4 | 6.4 | 20 | 1/4" |
| Disk | | | | | | | | | | | |
| MP6151 | 14,000 | 5" | 7/16"-20 | 6 5/16 | 160 | 2.1 | .95 | 3/8 | 10 | 22 | 1/4" |

GENERAL
 Air Inlet 1/4" NPT
 Use 1/4" (6.4 mm) I.D. hose
 All tools performance rated @ 90psi (620 kPa) air pressure.

STANDARD EQUIPMENT
 Owners Manual
 Parts Sheet
 MP4415: 57435 5" pad

OPTIONAL ACCESSORIES
 6" pad for model MP4415 - No. 57436
 60538 Master Guard oil (4 oz.)
 60539 Master Guard oil (1 qt.)
 63593 8' Hose whip
 22034 Hose line oiler

