

Vacuums

Air Vacs

- Moves water fast. Powerful motor delivers 116" water lift, 110 SCFM flow, and 60 gpm water pick-up capacity
- Low noise
- Lasts longer with little maintenance. No moving parts
- Increased power and efficiency from venturi system
- Overflow valve standard with all units
- Fine material filtering, down to 5 micron.
- Safe because it uses no electricity. Pick-up wet or dry and in other hazardous conditions*
- Cast aluminum epoxy coated heads for maximum corrosion resistance
- Recommended air supply hose size 1/2" I.D.



***CAUTION:** VACUUM MUST BE GROUNDED AND CONDUCTIVE HOSE USED TO CONTROL STATIC ELECTRICITY.

| Model Number | Description | Pick-up Hose | Water Lift | Flow S.C.F.M. | Weight lbs | C.F.M. @ 90 PSIG | Inlet | Standard Equipment |
|--------------|--|--------------|------------|---------------|------------|------------------|-------|---|
| MP8000 | 6 Gallon Wet/Dry Air Vac | 1 1/2" | 116" | 110 | 19.3 | 5.5 | 3/8" | 10' x 1 1/2" Vinyl hose #710040 Two Stage filter cartridge #718460 |
| MP8001 | 20 Gallon Wet/Dry Air Vac | 1 1/2" | 116" | 110 | 39.5 | 5.5 | 3/8" | 10' x 1 1/2" vinyl hose #710040 Two Stage filter cartridge #718461 Extra Heavy Duty 3 Wheel Dolly |
| MP8002 | 55 Gallon Wet/Dry Air Vac (Tank not included) | 1 1/2" | 116" | 110 | 18.5 | 5.5 | 3/8" | 10' x 1 1/2" vinyl hose #710040 Two Stage filter cartridge #718462 |

NOTE: Foam Muffler 80098300 used on all vacuums to reduce noise.

