

Screwdrivers

Direct Drive

- Torque Range
Up to 120 In. Lbs
Up to 13 Nm
- Reversible
- 1/4" Hex Quick Change
- 2 Step Throttle
- High parts interchangeability
- Side to center 13/16" (20.64 mm)
- 1/4" Hex Quick Change chuck



| Model Number | Wood Screws (in oak) | Thread Cutting Screws | Machine Screws | Sheet Metal Screws | Max Free RPM | Torque Rating | | | | Length | | Weight | |
|--------------|----------------------|-----------------------|----------------|--------------------|--------------|---------------|------|-----------|-----|--------|-----|--------|-----|
| | | | | | | Hard Slam | | Soft Pull | | in. | mm | lbs. | kg |
| | | | | | | In. Lbs. | Nm | In. Lbs. | Nm | | | | |
| MP2402 | — | — | #6 | #6 | 2800 | 28 | 3.2 | 20 | 2.3 | 5.5 | 140 | 1.7 | .8 |
| MP2406 | #8 | #8 | #10 | #10 | 1100 | 70 | 7.9 | 52 | 5.9 | 6.7 | 170 | 2.0 | .9 |
| MP2456 | #14 | 1/4" | 5/16" | 5/16" | 1100 | 120 | 13.6 | 85 | 9.4 | 7.5 | 190 | 2.6 | 1.2 |
| MP2453 | #12 | 1/4" | 1/4" | 1/4" | 1800 | 75 | 8.3 | 55 | 6.1 | 5.6 | 168 | 2.2 | .99 |
| MP2458 | #8 | #8 | #10 | #10 | 2800 | 65 | 7.2 | 30 | 3.3 | 6.6 | 168 | 2.2 | .99 |

GENERAL:
Air Inlet 1/4" NPT
Use 1/4" (6.4 mm) I.D. hose
All tools performance rated @ 90psi (620 kPa) air pressure.

STANDARD EQUIPMENT
Owners Manual
Parts Sheet

OPTIONAL ACCESSORIES
60538 Master Guard oil (4 oz.)
60539 Master Guard oil (1 qt.)
63593 8' Hose Whip 1/4" I.D.
22034 Hose Line Oiler
Tune-up kit, see page 56

