

- Torque Range
Up to 140 In. Lbs
Up to 15 Nm
- Reversible
- 1/4" Hex Quick Change
- Balanced design offers easy handling and control to reduce operator fatigue
- High parts interchangeability
- Side to center 13/16" (20.64 mm)



FASTENING

Model Number	Wood Screws (in oak)	Thread Cutting Screws	Machine Screws	Sheet Metal Screws	Max Free RPM	Torque Rating				Length		Weight	
						Hard Slam		Soft Pull		in.	mm	lbs.	kg
						In. Lbs.	Nm	In. Lbs.	Nm				
MP2464	#8	#8	#10	#10	2800	75	8.5	30	3.4	6.6	168	2.5	1.1
MP2465	#14	1/2"	3/4"	1/4"	1800	100	11	45	5.1	6.6	168	2.5	1.1
MP2465SR	#14	1/2"	3/4"	1/4"	1800	120	13.6	54	6.1	6.6	168	2.5	1.1
MP2416	#12	1/4"	1/4"	1/4"	1100	100	11.3	52	5.9	6.6	168	2.2	1.0
MP2462-M	#14	1/4"	5/16"	5/16"	1100	140	15.9	85	9.6	8.1	205	3.1	1.4

GENERAL:
Air Inlet 1/4" NPT
Use 1/4" (6.4 mm) I.D. hose
All tools performance rated @ 90psi (620 kPa) air pressure.

STANDARD EQUIPMENT
Owners Manual
Parts Sheet

OPTIONAL ACCESSORIES
60538 Master Guard oil (4 oz.)
60539 Master Guard oil (1 qt.)
63593 8' Hose Whip 1/4" I.D.
22034 Hose Line Oiler

WARNING: Face & eye protection must be worn while operating power tools, per ANSI B186.1. Cutting tool maximum speed rating must be equal or exceed speed of air tool @ 90 psi (620 kPa). Follow cutting tool manufacturer's mounting & operating instructions.



It is the user's responsibility to refer and comply with ANSI B7.1