

Screwdrivers

Adjustable Clutch

- Torque Range
12 - 140 In. Lbs
1.4 - 15 Nm
- Reversible
- 1/4" Hex Quick Change
- 2 Step Throttle, built in speed regulator (MP2474)
- Maximum parts interchangeability
- Extra-heavy engaging jaws



MP2477



MP2474

FASTENING

Model Number	Screw Size		Max. Free RPM	Torque				Length		Weight		Torque Range w/Light Torque Spring			
	in.	mm		Hard Slam		Soft Pull		in.	mm	lbs.	kg	Hard Slam		Soft Pull	
				In. Lbs.	Nm	In. Lbs.	Nm					In. Lbs.	Nm	In. Lbs.	Nm
Pistol Grip															
MP2422	#8	M4	2800	12-28	1.4-3.2	8-18	.9-2.0	6.3	159	2.1	1.0				
MP2426	#10	6	1100	30-80	3.4-9.1	20-50	2.3-5.7	7.5	190	2.4	1.1				
MP2470	#10	5	2800	20-75	2.3-8.5	12-30	1.4-3.4	8.5	216	2.9	1.3				
MP2477	#10	6	1800	37-100	4.2-11	30-45	3.4-5.1	7.8	197	2.6	1.2				
MP2472	1/4"	7	1100	20-140	2.3-15	17-85	1.9-9.6	9.1	232	3.4	1.5	4-22	.45-2.5	4-17	.45-1.9
Inline															
MP2474	#10	6	1800	37-100	4.2-11	30-45	3.4-5.1	10.1	257	2.8	1.3	4-30	.45-3.4	4-15	.45-1.9

GENERAL:

Air Inlet 1/4" NPT
Use 1/4" (6.4 mm) I.D. hose
All tools performance rated @ 90psi (620 kPa) air pressure.

STANDARD EQUIPMENT

Suspension bail (lever style only)
Clutch adjustment wrenches
Owners Manual

Parts Sheet

Standard Clutch Spring
9111500 MP2470, MP2473
8620800 MP2471, MP2472, MP2474, MP2475
70414700 MP2422
70414800 MP2424
70414900 MP2426

OPTIONAL ACCESSORIES

60538 Master Guard oil (4 oz.)

60539 Master Guard oil (1 qt.)
63593 8' Hose Whip 1/4" I.D.
22034 Hose Line Oiler
Light Optional Clutch Spring (5-20 in. lb.)
9111500 MP2471, MP2472, MP2474
70414700 Blue 8-25 in.lb.
Optional Clutch Springs for MP2422 - MP2426
70414800 Copper 20-50 in.lb.
70414900 Black 30-70 in.lb.

