

- Torque Range
5 - 140 In. Lbs
.6 - 15 Nm
- Reversible
- Torque externally adjusted
- 1/4" Hex Quick Change
- 2 Step Throttle
- Maximum parts interchangeability
- Drive and driven clutches are identical, inexpensive and easy to change
- Ball bearing supported output spindle
- Built-in speed regulator – MP2433
- Side to center 13/16" (20.64 mm)



MP2436



MP2433

FASTENING

Model Number	Wood Screws (in oak)	Thread Cutting Screws	Machine Screws	Sheet Metal Screws	Max Free RPM	Torque Rating				Length		Weight	
						Hard Slam		Soft Pull		in.	mm	lbs.	kg
						In. Lbs.	Nm	In. Lbs.	Nm				
Pistol Grip													
MP2432	#8	#8	#10	#10	2800	35-75	4-8.5	5-30	.6-3.4	8.5	216	2.9	1.32
MP2436	#12	1/4"	#10	1/4"	1800	17-100	1.9-11	5-45	.6-5.1	7.6	194	2.6	1.20
MP2437	#14	1/4"	1/4"	5/16"	1100	5-140	.6-15	5-85	.6-10	8.4	213	3.0	1.40
Inline													
MP2433	#12	1/4"	#10	1/4"	1800	17-100	1.9-11	5-45	.6-5.1	10.2	257	2.9	1.32

GENERAL:

Air Inlet 1/4" NPT
Use 1/4" (6.4 mm) I.D. hose
All tools performance rated @ 90psi (620 kPa) air pressure.

STANDARD EQUIPMENT

Owners Manual
Parts Sheet
Suspension Bail

OPTIONAL ACCESSORIES

60538 Master Guard oil (4 oz.)
60539 Master Guard oil (1 qt.)
63593 8' Hose Whip 1/4" I.D.
22034 Hose Line Oil

