

Impact Nutrunners

Reversible

- High power to weight ratio
- Speed of a screwdriver, power of an impact
- Ideal for soft joint applications
- 4 built-in speed control regulator positions for varying torque output for MP2264; 3 positions for the MP2265
- Smooth and efficient impact mechanism creates no torque reaction
- Compact clutch design
- 100% ball bearing design
- Reversible
- Detachable belt clip (MP2264, MP2265)



MP2264



MP2265



MP2266

FASTENING

Model Number	Bolt Capacity		Max Free RPM	Blows Per Minute	Torque Range		Weight		Drive In.
	in.	mm			Ft. Lbs.	Nm	lbs.	kg	
Pistol									
MP2264	1/2"	10	10,000	1700	10-65	13.5-102	2.2	1	1/4 QC
MP2265	1/2"	10	10,000	1400	10-55	13.5-75	2.2	1	3/8 SQ*
Inline									
MP2266	1/2"	10	9,500	1700	10-65	14.0-88	2.2	1	1/4 QC

GENERAL:
 Air Inlet 1/4" NPT
 Use 1/4" (6.4 mm) I.D. hose
 All tools performance rated @ 90psi (620 kPa) air pressure.
 *Pin retainer

STANDARD EQUIPMENT
 Owners Manual
 Parts Sheet

OPTIONAL ACCESSORIES
 60538 Master Guard oil (4 oz.)
 60539 Master Guard oil (1 qt.)
 22034 Hose Line Oiler
 70497000 Flow Regulator
 88007045 Trigger Assembly Kit, MP2264, MP2265





MP2271

MP2271

- Reversible
- Full power forward and reverse
- Unique butterfly throttle



MP2276

MP2276

- Lightweight yet durable composite housing
- Ergonomic grip for improved operator comfort
- Built-in power regulator with four settings
- Reversible


FASTENING

Model Number	Bolt Capacity		Free Speed RPM	Blows Per Minute	Torque Range		Weight		Square Drive In.
	in.	mm			Ft. Lbs.	Nm	lbs.	kg	
MP2271	3/8"	9.5	10,500	900	40-50	54-68	2.2	1.0	3/8 SQ
MP2276	1/2"	12	7,500	1100	70-90	95-122	3.1	1.4	3/8 SQ

GENERAL:
Air Inlet 1/4" NPT
Use 1/4" (6.4 mm) I.D. hose

All tools performance rated @ 90psi (620 kPa) air pressure.

WARNING: Face & eye protection must be worn while operating power tools, per ANSI B186.1. Cutting tool maximum speed rating must be equal or exceed speed of air tool @ 90 psi (620 kPa). Follow cutting tool manufacturer's mounting & operating instructions.

 It is the user's responsibility to refer and comply with ANSI B7.1

Impact Wrenches

Reversible

- Twin hammer anvil for reduced vibration
- High power to weight ratio
- Built in power regulator with four settings
- 100% ball bearing motor design
- Full power forward and reverse
- Smooth and efficient impact mechanism
- Compact clutch design
- Reversible



MP2295

MP2294

FASTENING

Model Number	Bolt Capacity		Max Free RPM	Blows Per Minute	Torque Range		Weight		Square Drive In.
	in.	mm			Ft. Lbs.	Nm	lbs.	kg	
MP2294	3/4"	20	6,500	1400	37-370	50-502	5.3	2.4	1/2 (ring ret.)
MP2295	3/4"	20	6,500	1400	37-370	50-502	5.3	2.4	1/2 (pin ret.)

GENERAL:

Air Inlet 1/4" NPT
 Use 1/4" (6.4 mm) I.D. hose
 All tools performance rated @ 90psi (620 kPa) air pressure.

STANDARD EQUIPMENT

Owners Manual
 Parts Sheet

OPTIONAL ACCESSORIES

60538 Master Guard oil (4 oz.)
 60539 Master Guard oil (1 qt.)
 63593 8' Hose whip
 22034 Hose line oiler



It is the user's responsibility to refer and comply with ANSI B7.1

WARNING: Face & eye protection must be worn while operating power tools, per ANSI B186.1. Cutting tool maximum speed rating must be equal or exceed speed of air tool @ 90 psi (620 kPa). Follow cutting tool manufacturer's mounting & operating instructions.