



MP5161



MP5164

MP5168 Kit



- 3,000 - 4,000 blows per minute
- Rated for continuous production use
- Precision feathering throttle for positive bit control
- 360° exhaust deflector. No blow back of chips, air, dust
- Patented interlock quick-change spring holds bits securely, permits easy, quick bit changes
- Replaceable steel nose bushing saves on cost of replacing complete barrel (MP5164 and MP5168)
- Side to center 13/32" (27.8mm)

CUTTING & PERCUSSION

Model Number	Blows Per Minute	Bore		Stroke		Length		Net Weight	
		in.	mm	in.	mm	in.	mm	lbs.	kg
MP5161	4000	.75	19	1.9	49	7.0	178	3.4	1.5
MP5164	3000	.75	19	2.7	68	8.1	206	4.0	1.8
MP5168	3000	.75	19	2.7	68	8.1	206	9.0	4.1

GENERAL
 Air Inlet 1/4" NPT
 Use 1/4" (6.4 mm) I.D. hose
 All tools performance rated @ 90psi (620 kPa) air pressure.

STANDARD EQUIPMENT
 MODELS MP5161 AND MP5164
 5861600 Quick change spring
 Owners manual
 Parts sheet

MODEL MP5168 CHISEL KIT
 MP5164 Power Chisel
 5861600 Quick change spring
 9253900 Undercoat scraper
 9253500 Sheet metal cutter
 9254000 Tapered punch
 9254500 9" Flat Chisel
 9254600 Chisel blank
 Owners manual
 Parts sheet

