

3/8" Sq. Dr. Socket Sets, Metric

6 Point




APS312M • 12 piece, standard length:
7mm, 8mm, 9mm, 10mm, 11mm, 12mm, 13mm, 14mm, 15mm, 16mm, 17mm, 18mm

APS312LM 12 piece, long length:
7mm, 8mm, 9mm, 10mm, 11mm, 12mm, 13mm, 14mm, 15mm, 16mm, 17mm, 18mm

Universal Wrenches 3/8" Sq. Dr., Metric

6 Point



Part Number 6 Point	Hex Opening mm	Overall Length (A) mm	Socket Length (B) mm	Socket Diameter (C) mm	Nose End Diameter (D) mm	Clearance Depth (E) mm
SA-36-10m •	10	48	20.6	19.1	15.1	9.5
SA-37-12m •	12	51	23.8	22.2	17.5	10.3
SA-37-13m •	13	52	25.4	22.2	17.5	11.9
SA-37-14m •	14	54	27.0	22.2	19.1	13.5
SA-38-15m •	15	56	28.6	25.4	19.8	14.3
SA-38-17m •	17	59	31.8	25.4	25.4	17.5
SA-38-18m •	18	59	31.8	25.4	25.4	17.5

Universal wrenches must not be used with impact drivers. Maximum operating angle is 30°.

3/8" Sq. Dr. Universal Wrench Set, Metric

6 Point



APU37M 7 piece, standard length:
10mm, 12mm, 13mm, 14mm, 15mm, 17mm, 18mm

3/8" Sq. Dr. Universal Wrenches, Metric - Extension

6 Point Standard and Tension Type




Part Number Standard	Part Number Tension	Hex Opening mm	Shank Length (A) mm	Socket Length (B) mm	Socket Diameter (C) mm	Nose End Diameter (D) mm	Clearance Depth (E) mm
KA-6-10m-4 •	-	10	102	20.6	19.1	15.1	9.5
KA-6-10m-6 •	KD-6-10m-6 •	10	152	20.6	19.1	15.1	9.5
KA-6-10m-9 •	KD-6-10m-9 •	10	229	20.6	19.1	15.1	9.5
-	KD-6-10m-12 •	10	305	20.6	19.1	15.1	9.5
-	KD-7-11m-6	11	152	23.8	22.2	15.9	10.3
KA-7-11m-12	KD-7-11m-12	11	305	23.8	22.2	15.9	10.3
KA-7-12m-4 •	-	12	102	23.8	22.2	17.5	10.3
KA-7-12m-6 •	KD-7-12m-6 •	12	152	23.8	22.2	17.5	10.3
KA-7-12m-9 •	KD-7-12m-9 •	12	229	23.8	22.2	17.5	10.3
KA-7-12m-12	KD-7-12m-12 •	12	305	23.8	22.2	17.5	10.3
KA-7-13m-3 •	-	13	76	25.4	22.2	17.5	11.9
KA-7-13m-4 •	-	13	102	25.4	22.2	17.5	11.9
KA-7-13m-6 •	KD-7-13m-6 •	13	152	25.4	22.2	17.5	11.9
KA-7-13m-9 •	KD-7-13m-9 •	13	229	25.4	22.2	17.5	11.9
KA-7-13m-12 •	KD-7-13m-12 •	13	305	25.4	22.2	17.5	11.9
KA-7-14m-6 •	KD-7-14m-6 •	14	152	27.0	22.2	19.1	13.5
-	KD-7-14m-9 •	14	229	27.0	22.2	19.1	13.5
KA-8-15m-3 •	-	15	76	28.6	25.4	19.8	14.3
-	KD-8-15m-6 •	15	152	28.6	25.4	19.8	14.3
KA-8-15m-9 •	KD-8-15m-9 •	15	229	28.6	25.4	19.8	14.3
KA-8-15m-12 •	KD-8-15m-12 •	15	305	28.6	25.4	19.8	14.3

Universal wrenches must not be used with impact drivers. Maximum operating angle is 30°.

3/8" Sq. Dr. Socket Head Bits, Metric

Complete, Adapter Only, Insert Only



Complete	Part Number Adapter Only	Part Number Insert Only	Hex Size	Overall Length In. mm	Length of Insert (A) In. mm
SZ-3-7-4mm •	SC-314 •	SZ-7-4mm •	4mm	2 1/4 57	1 3/8 35
SZ-3-7-5mm •	SC-314 •	SZ-7-5mm •	5mm	2 1/4 57	1 3/8 35
SZ-3-7-6mm •	SC-314 •	SZ-7-6mm •	6mm	2 1/4 57	1 3/8 35
SZ-3-7-8mm •	SC-314 •	SZ-7-8mm •	8mm	2 1/4 57	1 3/8 35
SZ-3-7-10mm •	SC-314 •	SZ-7-10mm •	10mm	2 1/4 57	1 3/8 35

See page 19 for more 3/8" drive complete socket head bits.

• Indicates a commonly requested item that is either in stock or has a max typical leadtime of 4 weeks from the factory. No minimum on these items.