

# Socket Retaining Rings

## Plastic Ring With Steel Insert



Part Number	Drive	Inside Diameter	
		In.	mm
10005S	3/4" Square	1 1/4	31.8
10032S•	3/4" Square	1 7/16	36.5
10034S•	3/4" Square	1 5/8	41.3
10008S•	1" Square	1 3/4	44.5
10010S•	1" Square	2	50.8
10015S•	1" Square	2 1/8	54.0
10016S•	1" Square	2 1/4	57.2
10017S	1" Square	2 1/2	63.5
10019S	1" Square	2 5/8	66.7
10020S	1 1/2" Square	2 7/8	73.0
10025S	1 1/2" Square	3 3/8	85.7

## Metal Ring



Part Number	Drive	Inside Diameter	
		In.	mm
MET-1301C•	3/8" Square	.677	17.2
MET-1302C•	3/8" Square	.771	19.6
MET-1401C•	1/2" Square	.885	22.5
MET-1402C•	1/2" Square	1.086	27.6
MET-1600C•	3/4" Square	1.594	40.5
MET-1800C•	1" Square	1.948	49.5

# Adapters

## #130-A Yankee Drive for Spiral Type Driver



Part Number	Male Square In.	Overall Length		Shank Diameter	
		In.	mm	In.	mm
YK-250	1/4	1 15/16	49	.277	7.0
YK-370•	3/8	2 3/16	56	.277	7.0
YK-500	1/2	2 5/16	59	.277	7.0

## #131-A Yankee Drive for Spiral Type Driver



Part Number	Male Square In.	Overall Length		Shank Diameter	
		In.	mm	In.	mm
YK-501	1/2	2 5/16	59	.310	8.0

## #135-A Yankee Drive for Spiral Type Driver



Part Number	Male Square In.	Overall Length		Shank Diameter	
		In.	mm	In.	mm
YK-252	1/4	1 15/16	49	.215	5.5
YK-372•	3/8	2 3/16	56	.215	5.5
YK-502	1/2	2 5/16	59	.215	5.5

## Female Threaded Adapters



Part Number	Female Thread	Male Square In.	Type of Lock
TH-377	3/8"-24	3/8	Pin
TH-501	3/8"-24	1/2	Pin
TH-378	1/2"-20	3/8	Pin
TH-502	1/2"-20	1/2	Pin

## Male Threaded Adapters



Part Number	Male Thread	Hex Drive
TN-24	3/8"-24	7/16
TM-20•	1/2"-20	1/4
TN-20•	1/2"-20	7/16

• Indicates a commonly requested item that is either in stock or has a max typical leadtime of 4 weeks from the factory. No minimum on these items.